



CAN-AM LEATHER JACKET

Supple jacket with stretchable fabric inserts for easy movement. Numerous pockets and removable insulation. Also available in ladies' fit.



SUMMER MESH RIDING JACKET

Designed for warm days. Features light, removable liner, wear-resistant mesh and reflective details. Also available in men's cut.



CAN-AM ST-1 HYBRID HELMET

Lightweight motorcycle helmet-inspired design with multiple configurations. Pictured: jet-ventilated jaw for enhanced protection and comfort.



RAIN JACKET

Features additional liner hood for use under helmet to prevent water infiltration. Reflective details for visibility. Rain pants also available.

SPECIFICATIONS

ROTAX ENGINE

Manufacturer	BRP-Rotax
Type	990 V-Twin
Displacement	998cc (60.90 cu. in.)
Bore	97 mm (3.82 in.)
Stroke	68 mm (2.68 in.)
Cylinder	2
Valves per cylinder	DOHC 4
Max output	106 hp @ 8500 RPM (79 kW @ 8500 RPM)
Max torque	77 lb.-ft. @ 6250 RPM (104.3 Nm @ 6250 RPM)
Compression ratio	10.8:1
Ignition type	Electronic ignition with dual output coil
Lubrication	5W40 semi-synthetic oil
Exhaust system	2-into-1 with catalytic converter
Cooling	Liquid-cooled
Injection	Multi-point EFI with 57 mm-diameter throttle bodies

DRIVE TRAIN

Gear box	5-Speed manual (SM5) with transmission-based reverse
Optional gear box	5-Speed semi-automatic (SE5) with transmission-based reverse
Final drive	28/79 ratio final drive with Kevlar-reinforced drive belt
Clutch	Wet, multi-plate, manual operation through a hydraulic piston

ELECTRIC EQUIPMENT

Magneto	500 Watts
Starter	Electric
Battery	Sealed maintenance-free, 12V, 21 Amp

GEOMETRY

Front suspension	Double A-Arm with anti-roll bar
Front suspension travel	5.67 in. (145 mm) shocks
Rear suspension	Swing-arm with monoshock
Rear suspension travel	5.67 in. (145 mm) with adjustable cam
Chassis type	SST Spyder (Surrounding Spar Technology)
Steering	DPS (Dynamic Power Steering)

TIRES & WHEELS

Front tire	KR21 165/65R14
Front nominal pressure	13-17 psi (90-117 kPa)
Rear tire	KR21 225/50R15
Rear nominal pressure	26-30 psi (179-207 kPa)
Wheel size, front	Aluminum 14x5 (355x127)
Wheel size, rear	Aluminum 15x7 (381x178)

BRAKES

Type	Foot-actuated, fully integrated hydraulic 3-wheel braking system
Front braking system	4 piston calipers with 10.2 in. x 0.25 in. (260 mm x 6 mm) discs
Rear braking system	Single-piston caliper with 10.2 in. x 0.25 in. (260 mm x 6 mm) disc
EBD	Electronic Brake Distribution
ABS	Anti-lock Braking System
Parking brake	Mechanical, foot actuated to the rear caliper

SAFETY & SECURITY

VSS	Vehicle Stability System
ABS	Anti-lock Braking System
TCS	Traction Control System
SCS	Stability Control System with roll-over mitigation
DPS	Dynamic Power Steering
DESS	Digitally Encoded Security System

VEHICLE DIMENSIONS & WEIGHTS

Dry vehicle weight	699 lb. (317 kg)
Front storage capacity	11.62 US gal. (44 l)
Front max load capacity	30 lb. (15.9 kg)
Total vehicle load allowed	440 lb. (200 kg)
Fuel capacity	7.13 US gal. (25 l)
Oil capacity	1.19 US gal. (4.5 l)
Coolant capacity	0.85 US gal. (3.2 l)
GVWR	1,188 lb. (540 kg)
Ground clearance	4.5 in. (115 mm)
Vehicle overall height	45.1 in. (1,145 mm)
Vehicle overall length	105 in. (2,667 mm)
Vehicle overall width	59.3 in. (1,506 mm)
Seat (top) height	29 in. (737 mm)
Wheel base	68 in. (1,727 mm)
Wheel track, front	51.5 in. (1,308 mm)
Type of gas	Unleaded, 87 octane minimum

COLOR CHOICES

Full Moon Silver
Roadster Red
Quantum Blue
Millennium Yellow
Pearl White (RS-S Special Edition only)

FEATURES

	RS	RS-S
Sport windshield	X	X
11.62 US gal. (44 l) front storage	X	X
Parking brake	X	X
Digitally Encoded Security System	X	X
Speedometer	X	X
Tachometer	X	X
Electric fuel gauge	X	X
Dual trip meters	X	X
Engine temperature	X	X
Ambient temperature	X	X
Gear position indicator	X	X
6-Spoke custom wheel kit	•	X
Custom white trim seat	•	X
Spyder rolling travel bag	•	X
Custom decals	NA	X
Exclusive pearl white color	NA	X
Two-year warranty	X	X

X – Standard Feature • – Optional Feature